

TECHNICAL DATA SHEET
Ref. 530011
UNIPOLAR ELECTROMAGNETIC
BATTERY MASTER SWITCH
24VDC / 300A



GENERAL CHARACTERISTICS

Protection degree: IP65
 Ambient temperature: -40°C to +80°C
 Weight: 1.0 Kg approx.
 Contacts: Double cut copper
 Connections: not polarized
 Is working in all positions

FIELDS OF APPLICATION

Handling vehicles, industrial vehicles,
 agriculture machinery, navy...

CONTROL CIRCUIT

Breakaway starting current: 4,5 A (20 ms)
 Holding current: 0,25 A
 Absorbed power from the coil: <6 W
 Guaranteed interlocking tension: 18 V
 Disengaging tension: ≤ 6 V
 Connections by M5 terminals
 Tightening torque: 0.4 +/- 0.2 daN·m

POWER CIRCUIT

Connection: M10 terminals
 Tightening torque: 1.4 +/- 0.2 daN·m
 Type: normally open unipolar
 Max. using tension: 48 V
 Capacity:
 300 A in continuous
 2400 A during 1 second
 600A during 20 seconds

PARTICULAR CHARACTERISTICS:

Black galvanised finishing.
 Corrosion test: 200 h salt spray resistance



P.I. El Raiquer, C/ El Raiquer, s/n, NAVE Nº21-22
 08170 MONTORNÈS DEL VALLÈS
 BARCELONA (SPAIN)
 Tel. : + 34.93.544.44.80 - Fax : + 34.93.544.44.90
www.cormar.es - info@cormar.es

Size diagrams

